

COCell 587Ah

Prismatic LFP cell optimised for use in stationary ESS



Preliminary

Prismatic LFP cell with very high cyclic lifetime and reliable safety characteristics.

Specially optimised for use in stationary battery storage systems with the highest requirements on safety, reliability and performance. Suitable for industrial, utility, and grid-serving applications.

- Product certifications*: IEC 62619, UL 9540A, UL 1973, GB/T 36276, UN 38.3
- Company certifications: ISO 9001, ISO 14001, ISO 45001, SA 8000
- Environmental Compliance*: RoHS, REACH, Regulation (EU) 2023/1542, Cobalt free

High safety

- HiTHIUM-developed prismatic LFP cell with high thermal stability.
- No fire or explosion during nail penetration and crush tests
- Ultra wide operating temperature range

Low LCOS (Levelised Cost of Storage)

■ Very high cyclic lifetime ≥ 11.000 cycles, thanks to advanced material and process technologies

Flexible and versatile use

COCell 587 Ah

ELECTRICAL **Nominal Voltage**

Operating Voltage

Max. Self-discharge Rate

Prismatic LFP cell optimised for use in stationary ESS

^{co} Cell 587Ah	2.0	
	C HTHIUM	

87 Ah ^{1, 2}
.878,4 Wh ^{1, 2}
FePO ₄ (LFP)
11.000
185 Wh/kg
413 Wh/L
T587P050A

3,2 V ^{1,2}

T > 0°C 2,50 ... 3,65 V $T \le 0^{\circ}C \quad 2,00 \dots 3,65 V$

Dimensions (L x W x H) 286 x 73,50 x	x 216,3 mm
Type Prismatic	
Weight 10,20 kg +/-	0,2
Volume 4,55 L	

TEMPERATURE RANGE		
Charging	0°C 60°C	
Discharging	-30°C 60°C	
Storing (Recommended)	-20°C 35°C	

PRODUCT CERTIFICATIONS*		
Safety Certificates	IEC 62619, UL 9540A, UL 1973 GB/T 36276	
Safe Transportation	UN 38.3	

ENVIRONMENTAL*	
Compliance	RoHS, REACH, Cobalt free
Battery Regulation (EU)	2023/1542

COMPANY CERTIFICATIONS

ISO 9001, ISO 14001, ISO 45001, SA 8000

HiTHIUM Energy Storage Technology Deutschland GmbH

Website: https://hithium.com | Email: Contact@hithium.de Address: Landsberger Str. 155, 80687 Munich, Germany

Xiamen HiTHIUM Energy Storage Technology Co., Ltd. Address: HiTHIUM Industrial Park, Tongxiang High Tech Zone, Xiamen, Fujian, China | Email: hithium@hithium.com





Nominal Continuous Charge Rate	0,5 P	S
Nominal Continuous Discharge Rate	0,5 P	E
		C
¹ 25°C +/- 2,0 ² 27% SOC [*] The certifications are in-pro	ogress.	E

3 %/month ^{1, 2}

Document is subject to regular updates, corrections, and improvements. Kindly check you are using latest version. Picture for illustration purpose only.